
Gila Window Film Application Solution

*Gila Window
Film
Application
Solution*

*Downloaded from
db.whlarchitecture.com
by Davila & Andrews*

REVITALIZE YOUR SPACE WITH THE GILA WINDOW FILM APPLICATION SOLUTION

Window films have become an increasingly popular choice for homeowners and renters looking to improve energy efficiency, reduce glare, and enhance privacy without the significant expense of replacing windows. Among the many brands available, Gila stands out as a trusted name, offering a wide range of films designed

for various needs—from heat control to decorative privacy. However, even the best film can fail if the installation is not performed correctly. This is where understanding the complete **Gila Window Film Application Solution** becomes essential. Whether you are a seasoned DIY enthusiast or a first-time applicator, mastering the application process is the key to achieving a professional, bubble-free finish that lasts for years. This guide will walk you through every

step, from preparation to final curing, ensuring you get the most out of your Gila window film investment.

UNDERSTANDING THE GILA WINDOW FILM PRODUCT RANGE

Before diving into the application process, it is important to understand what you are working with. Gila offers several categories of window film, each with a unique construction and specific application nuances. While the basic installation method remains similar across the lineup, knowing your specific product type helps manage expectations and technique.

Heat Control and Solar Films

These are Gila's most popular offerings. They are designed to reject a significant percentage of solar heat and block up to 99% of harmful UV rays. Films such as the Gila Heat Control Platinum series often use advanced adhesive technologies that activate during application. These films tend to be slightly thicker and may require a bit more solution and a firmer squeegee stroke to seat properly.

Privacy and Decorative Films

For those seeking seclusion or aesthetic enhancement, Gila offers frosted, patterned, and even stained-glass-style films. These are typically static-cling or low-tack adhesive products. The application solution for these films is critical because it allows you to slide the film into perfect position before the adhesive sets. Because they are often used on interior windows or glass doors, a flawless application is visually paramount.

Safety and Security Films

Gila's safety films are thicker and designed to hold glass shards together in the event of an impact. Applying these films requires a robust solution mixture and careful handling. The extra thickness means you must pay close attention to edge sealing and air removal, as trapped moisture takes longer to evaporate through the heavier material.

WHY THE APPLICATION SOLUTION MATTERS

Many people assume

that applying window film is simply a matter of peeling and sticking. This is a mistake. The **Gila Window Film Application Solution** is not just a lubricant; it is a critical part of the installation chemistry. The solution serves three primary purposes:

- **Lubrication:** It allows the film to slide effortlessly across the glass so you can align it perfectly without the adhesive sticking prematurely.
- **Activation:** For many Gila films, the water-based solution helps activate the pressure-sensitive adhesive, allowing it to bond aggressively to

the glass once the water is removed.

- **Contamination**

Control: The solution helps float microscopic dust particles away from the adhesive, preventing pesky bumps and specks from being locked under the film.

Using plain tap water often leads to hard water spots, mineral deposits, and poor adhesive performance. Gila recommends a specific mixture of baby shampoo or a dedicated slip solution to ensure the perfect balance of lubrication and tack.

PREPARING YOUR TOOLS AND

WORKSPACE

Preparation is the single most important factor in a successful application. Rushing this phase guarantees frustration later. Before you even open the box containing your Gila film, gather the following items to create your complete application solution kit.

Essential Tools for the Job

1. **Gila application solution:** You can purchase Gila's own pre-mixed solution or mix your own using one teaspoon of clear, non-conditioning

baby shampoo per 32 ounces of distilled water.

2. **Squeegee:** Gila typically includes a small squeegee in the box, but a larger, professional-grade squeegee with a soft rubber edge is highly recommended for larger windows.
3. **Sharp utility knife or Gila cutting tool:** A sharp blade is non-negotiable. Dull blades cause jagged edges and can scratch the glass.
4. **Lint-free microfiber cloths:** Paper towels leave lint and dust. Use high-quality microfiber for

cleaning the glass and blotting edges.

5. **Spray bottles:**

You will need at least two bottles—one for clean water and one for your application solution.

6. **Blue tape:**

Useful for marking reference lines or holding trimmings in place.

Conditioning the Glass Surface

Cleanliness is next to godliness in the world of window film. Even a particle invisible to the

naked eye becomes a glaring imperfection once magnified by the film. Start by cleaning the window thoroughly with a razor blade scraper to remove paint splatters, hard water deposits, or old adhesive. Follow this with a vigorous wash using a mild detergent and water. Rinse completely. Finally, wipe the glass dry with a clean microfiber cloth. Just before you are ready to apply the film, mist the glass with your application solution and squeegee it off one final time to remove any static dust that has settled.

THE STEP-BY-STEP GILA WINDOW FILM APPLICATION PROCESS

With your workspace clean and your solution prepared, you are

ready for the main event. Follow these steps carefully to achieve a professional-grade finish using the **Gila Window Film Application Solution**.

Step 1: Measure and Cut the Film

Measure the width and height of your glass pane. Gila recommends adding roughly half an inch to both dimensions. This overage ensures you have enough film to cover the entire glass surface without leaving bare gaps at the edges. Use a sharp straightedge and a utility knife to cut the film on a clean, flat

surface. Handle the film by the edges only to avoid contaminating the adhesive with skin oils.

Step 2: Wet the Glass Generous ly

Spray your prepared Gila Window Film Application Solution liberally onto the interior surface of the window. Do not be shy here. The glass should be completely soaked. A generous amount of solution is what allows the film to be repositioned and prevents the adhesive from grabbing prematurely. If the

glass dries out during application, the film will stick instantly, and you will likely trap air bubbles or misalign the film.

Step 3: Remove the Liner and Wet the Adhesive

Carefully peel the clear polyester liner away from the adhesive side of the film. Immediately after removing the liner, spray the exposed adhesive with your application solution. This step is critical. The adhesive must be wet

before it touches the glass. This is the core of the **Gila Window Film Application Solution**

technique—keeping both surfaces wet ensures maximum slip and adjustability.

Step 4: Position the Film

Lift the wet film by the top two corners and place it against the wet glass. Because both the glass and the adhesive are slick with solution, you can slide the film around easily. Align the film so that it overlaps the window frame evenly on all sides. Do not worry about the excess overhang yet. Focus purely on getting the

film centered and square.

Step 5: Squeegee Out the Solution

This step requires patience and technique. Starting from the center of the film, use your squeegee to push the trapped solution outward toward the edges. Use firm, overlapping strokes. The goal is to force all the excess water and air out from beneath the film. As you squeegee, you will see the film bond tightly to the glass. Pay special attention to the edges, but do not push the film over the frame

stops yet.

Tip: If you see bubbles forming, do not panic. Lift the nearest edge of the film, spray more solution underneath, and re-squeegee the area. The solution gives you a second chance to fix mistakes.

Step 6: Trim the Excess Film

Once the film is fully seated and all major solution pockets are removed, it is time to trim the edges. Use a sharp utility knife and a steady hand. Cut along the edge of the window frame, following the glass contour. For most windows, a straight cut against the frame is

sufficient. For windows with rubber gaskets, you may need to trim slightly inside the gasket line. After trimming, use the squeegee to press the edges down firmly.

Step 7: Edge Sealing and Final Wipe

Wrap your squeegee in a microfiber cloth or use your finger wrapped in a cloth to run along the cut edges of the film. This ensures the edge is fully adhered and prevents lifting. Blot any residual solution that seeps out from the edges. Do not rub the

face of the film aggressively, as the film is still soft and can be scratched.

POST-APPLICATION CARE AND CURING

Applying the film is only half the battle. The curing process is where the adhesive fully dries and bonds to the glass. Understanding this phase ensures you do not ruin your hard work.

The Curing Timeline

Depending on the humidity and temperature, Gila window films typically take between 7 and 30 days to cure completely. During this

time, the remaining microscopic water molecules trapped in the adhesive evaporate. You may notice small water pockets or a slight haziness. This is normal. These will disappear as the film cures.

What to Avoid During Curing

- **Do not roll down the window:** If you applied film to a vehicle window or a sliding window, leave it closed for at least one week.
- **Avoid direct sunlight**

exposure immediately:

While the film is designed for heat rejection, the adhesive needs a moderate environment to set. Extreme heat can cause the water to turn to vapor too quickly, creating permanent bubbles.

- **Do not clean the film:** Wait at least 30 days before cleaning the film. Use only a soft cloth and a non-ammonia-based cleaner. Ammonia can degrade the adhesive and cause delamination.

TROUBLESHOOTING COMMON

ISSUES

Even with a perfect **Gila Window Film Application Solution**, things can go wrong. Here is how to address the most common problems.

Persistent Air Bubbles

If you have tiny bubbles that refuse to disappear after 48 hours, they are likely caused by dust specks trapped under the film. If they bother you, you can puncture the bubble with a pin and gently squeegee the air out. For larger bubbles, lift the film and re-wet the area.

Adhesive Residue or Sticky Edges

If the edges feel sticky after trimming, you likely did not squeegee enough solution out from under the edges. Use a damp cloth to gently clean the edges and then use a credit card wrapped in a cloth to press the edges down firmly.

Film Lifting at Corners

This usually happens when the corners were not trimmed properly

or when the glass was not cleaned well enough. Re-wet the corner with solution, lift the film gently, clean the glass again, and re-squeegee. If the corner continues to lift, a tiny drop of clear silicone can be used as a temporary fix, though this is rarely necessary with proper technique.

WHY PROFESSIONAL RESULTS START WITH THE RIGHT SOLUTION

The market is flooded with window film installation guides, but the one variable that consistently separates a mediocre job from a masterpiece is the quality and use of the application solution. The **Gila Window Film Application Solution** is specifically formulated to balance

slip and tack. When you use the correct mixture and apply it liberally, you give yourself a massive margin for error. You can adjust alignment, push out air bubbles with ease, and ensure the adhesive mates perfectly with the glass substrate.

Skipping the solution or using a substitute like dish soap can lead to residue buildup, poor adhesion, and even chemical reactions that degrade the film over time. Investing in the right solution—or mixing your own according to Gila's specifications—pays dividends in the longevity and appearance of your installation.

Environmental Considerations

Gila films themselves contribute to energy savings by reducing cooling loads in summer and retaining heat in winter. A proper application maximizes these benefits. When the film is installed correctly with the right solution, it creates an airtight bond that prevents air

infiltration at the edges. This seal is crucial for maintaining the thermal performance ratings of the film. A poorly applied film with lifted edges or trapped moisture will not perform as intended, negating the energy-saving potential of the product.

CONCLUSION

Applying window film is a rewarding DIY project that can transform the comfort and appearance of your home or office. While the task may seem daunting at